



June 16, 2025

Montebanc Management, LLC
Attn: Chip McBroom and Paul DeVenzio
400 NW Gilman Blvd., #2781
Issaquah, Washington 98027

Re: Geotechnical Engineering Report - Addendum

Johnson Residential Development
Kitsap County Parcel Numbers: 242601-3-018-2001, 242601-3-005-2006, and 242601-3-019-2000
Poulsbo, Washington
Project No. AS240561-03

Dear Mr. McBroom and Mr. DeVenzio:

Aspect Consulting, a Geosyntec company (Aspect), prepared a Geotechnical Engineering Report dated February 14, 2025 (Aspect, 2025), documenting our geologic hazard assessment and geotechnical engineering evaluation for the proposed residential development (Project) on three parcels north of State Route 305 in Poulsbo, Washington, known as Kitsap County (County) parcel numbers 232601-4-001-2009, 242601-3-003-2008, and 252601-2-047-2007 (collectively the Site).

We understand you are now contracted to purchase three additional County parcels: 242601-3-018-2001, 242601-3-005-2006, and 242601-3-019-2000, which collectively cover about 8 acres. These parcels are referred to as the Owl Ridge Parcels. Our additional scope of work included a geologic reconnaissance, the advancement of additional test pits to understand the subsurface soil and groundwater conditions, laboratory testing, and the associated analysis and this addendum.

Project Understanding

Current project plans for the Owl Ridge Parcels include about 26 residential parcels, a connector roadway from Sunrise Ridge Avenue NE from the northern property line near the northwest corner that will extend through the properties to the southern property line near the southeast corner, and associated utilities and infrastructure (Graphic 1; ESM, 2025).






Graphic 1. Current Project Plans (ESM, 2025)

The County’s geologic hazard map designates four hazards on the Owl Ridge Parcels (Graphic 2 below):

- A high landslide hazard, defined as steeper than 30 percent slopes, is present along the east side of the parcels.
- A limited area of moderate landslide hazard, defined as slopes between 15 to 30 percent is along the west property line, extending onto the previously evaluated property.
- A moderate seismic hazard covers a large area through the middle and east side of the parcels.

The City’s standard buffer requirement is 25 feet from the top, toe, and all edges of geologically hazardous areas and areas of geologic concern, unless otherwise specified. In our experience, a geotechnical report will be required by the City for the Project.



Graphic 2. County Geologic Hazards Map (County, 2025)

Existing Conditions

The Owl Ridge Parcels consists of three undeveloped parcels. The west parcel (242601-3-018-2001) is approximately 5 acres and measures about 440 feet north to south and 490 feet east to west, with Sunrise Ridge Avenue NE to the north. The central parcel (242601-3-005-2006) is approximately 2.5 acres and measures approximately 310 feet north to south and 345 feet east to west. The eastern parcel (242601-3-019-2000) is about 0.12 acres and measures approximately 140 feet north to south and 15 feet east-to-west (County, 2025).

The central parcel is developed with a one-story, 577-square-foot residence built in 1935 with a gravel access driveway from the south, near the central area of the parcel (Photograph 1). A stormwater pond is located in the southeast corner of the central parcel (Photograph 2).

An asphalt paved roadway (Sunrise Ridge Avenue NE) cuts through the parcels and other gravel and dirt roadways cross throughout the parcels. A gravel roadway along the southern boundary provides access to a residential property to the west while another roadway provides access along the eastern boundary to the north, Maple Hill Avenue NE.

Topography

The ground surface of the Owl Ridge Parcels slopes down to the south with about 90 feet of elevation loss and an average slope of about 27 percent (15 degrees).

Drainage

Water was observed in the stormwater pond. Outside the pond, no water seepage, springs, flowing water, evidence of past standing or flowing water, hydrophilic vegetation, or saturated soils were observed.



Photograph 1. Existing Residence on central parcel, view to the northwest, on April 17, 2025.



Photograph 2. Stormwater pond in southeast corner of central parcel, view to the east, on April 17, 2025.

Vegetation

Vegetation in the areas of more recent development (i.e., the roadways, stormwater pond, and residence), consists largely of alders, maples, scotch broom, grasses, and woody shrubs. Other areas contain more mature evergreens up to 40 inches diameter at breast height, and forest undergrowth of sword ferns and woody underbrush.

Subsurface Conditions

The geologic map (Haugerud and Troost, 2011) indicates the center of the Owl Ridge Parcels is underlain by Vashon Esperance Sand Member (Qve) with Vashon till (Qvt) to both the east and west. Landslide deposits (Qls) are mapped along the eastern property line and are described as a diamict of sand, gravel, silt, and soil transported in deep-seated landslides.

The Esperance Sand Member was an advance outwash material deposited in broad low areas and fluvial channels in front of the advancing 3,000-foot-tall Cordilleran Glacier icesheet at the end of the Vashon Stade of the Fraser Glaciation (about 13,000 to 16,000 years ago) and is generally described as a mostly quartzofeldspathic fine to medium sand, locally pebbly or with small amounts of gravel or silt with a dense/hard configuration. Vashon till was deposited directly under the glacier and is described as a diamict of dense to very dense silt, sand, gravel, cobbles, and boulders.

Although not mapped, human-placed fill would be expected due to the roadway and stormwater pond constructed on the parcels. Fill is human-placed materials that is often found in developed areas and can be highly variable.

Stratigraphy

On April 17, 2025, we oversaw the advancement of eight (8) test pits, designated ATP-15 through ATP-22, which terminated between 6 and 11 feet below ground surface (bgs). Detailed descriptions of the subsurface conditions and soil characteristics are provided in the exploration logs in Appendix A. The locations of the test pits are shown on Figure 2.

Below surficial topsoil, we encountered Vashon recessional outwash (Qgo) in test pit ATP-17 in the northwest corner of the Owl Ridge Parcels. Recessional outwash is a fluvial deposit laid down during the retreat of the Vashon-age glacier. The geologic map shows this unit about 2,300 feet northwest, in a lower lying area (Polenz et al, 2013). We did encounter this unit on the western adjacent parcel somewhat nearby to this location.

Two of the test pits, APT-18 and ATP-21, encountered Vashon till, in agreement with the geologic map. The remaining five test pits, ATP-15, ATP-16, ATP-19, ATP-20, and ATP-22, encountered pre-Vashon glaciolacustrine deposits with varying degrees of weathering. A geologic map presenting inferred geologic contacts based on our subsurface investigation is presented as Figure 3. A summary table of the units encountered at the respective depths is presented in Table 1 following the descriptions.

Topsoil: Topsoil refers to a unit that contains a high percentage of organics. We encountered topsoil at the ground surface in all of the test pits, extending from 0.5 to 1.8 feet bgs. The topsoil consisted of loose¹, dark brown silt (ML)² with sand, abundant wood debris, and roots.

Vashon till: Underlying the topsoil, Vashon till was encountered in two of the explorations, ATP-18 and ATP-22, and both test pits were terminated in this unit. It consisted of very dense, gray, silty sand (ML) with subrounded to faceted gravels socketed into the diamict structure.

Pre-Vashon Fines: Glaciolacustrine Deposits: Underlying the topsoil, glaciolacustrine deposits were encountered in the remaining five test pits to the depths explored. We interpreted the glaciolacustrine deposits to be part of the pre-Vashon silt (Qpf), in agreement with geologic mapped material in the ravine in the northwest corner of the Owl Ridge Parcels. The deposit consisted of medium dense to dense, sand with silt (SM) and silt with sand (SM) with varied degrees of weathering.

The upper horizon of the deposit has been highly weathered, underlain by a slightly less weathered horizon, and lastly underlain by a relatively unweathered horizon. The amount of weathering decreases with depth while the density of the material increases. The highly-weathered glaciolacustrine deposits are loose, moist to very moist, brown silt with sand (ML) with iron-oxide staining and few root fragments. The weathered glaciolacustrine deposits are dense, moist, gray brown silt with sand (ML) with 0.1- to 0.2-inch-thick iron-oxide stained sand partings. The relatively unweathered glaciolacustrine deposits are very dense, blue gray silt with sand (ML) with 0.1- to 0.2-inch-thick sand partings.

¹ Relative density was assessed at various depth intervals in the explorations qualitatively with a 0.5-inch-diameter, pointed steel T-probe, and qualitatively with a dynamic cone penetrometer test (DCPT).

² Soils were classified per the Unified Soil Classification System (USCS) in general accordance with ASTM International (ASTM) D2488, *Standard Practice for Description and Identification of Soils* (ASTM, 2022).

Table 1. Geologic Units Encountered

Exploration Number	Depth of Topsoil (feet bgs)	Depth of Vashon Recessional Outwash (feet bgs)	Depth of Vashon Till (feet bgs)	Depth of Highly-Weathered Glaciolacustrine (feet bgs)	Depth of Weathered Glaciolacustrine (feet bgs)	Depth of Glaciolacustrine Deposits (feet bgs)	Total Depth (feet bgs)
ATP-15	0-1	NE	NE	1-4	4-7	7-11	11
ATP-16	0-0.5	NE	NE	0.5-2	2-5	5-9.5	9.5
ATP-17	0-0.5	0.5-9.5	NE	NE	NE	NE	9.5
ATP-18	0-1	1-3	3-5	NE	NE	NE	5
ATP-19	0-0.5	NE	NE	0.5-2	2-3.5	3.5-9	9
ATP-20	0-0.5	NE	NE	0.5-2	2-3.8	3.8-8	8
ATP-21	0-1	NE	1-6	NE	NE	NE	6
ATP-22	0-1.8	NE	NE	1.8-3	3-8	8-8.5	8.5

Notes:

1. NE – not encountered

Groundwater

We encountered groundwater seepage from the sidewalls about 2 to 3 feet bgs in two test pits, ATP-15 and ATP-22. We interpreted the observed seepage to be perched groundwater and not representative of a regional groundwater table. A perched groundwater condition occurs when surface water percolates into the shallow subsurface and collects on relatively impermeable materials. In this case, the topsoil and highly-weathered glaciolacustrine units are considered low permeability units, while the glaciolacustrine deposits are essentially impermeable. Sand partings in the upper highly-weathered and weathered glaciolacustrine deposits allow water to move through the upper units and perch on top of the glaciolacustrine deposits.

Laboratory Testing Results

Geotechnical laboratory tests were conducted on six selected samples to characterize engineering and index properties. Four grain-size distributions and two fines content (particles passing the No. 200 sieve) analyses were completed, and the natural moisture contents of these soil samples were also determined and are presented on the test pit logs. The test methodology and results of all the laboratory testing are presented in Appendix B along with a summary table including the geologic unit classification.

Table 2. Summary of Geotechnical Laboratory Test Results

Exploration Number	Sample Depth (feet bgs)	Percent Gravel	Percent Sand	Percent Fines	Moisture Content (percent)	USCS ²	Geologic Unit
ATP-16	2	1	97	8	12.6	SP-SM	Highly Weathered Glaciolacustrine
ATP-16	5	NT ¹	NT ¹	66	21.5	ML	Weathered Glaciolacustrine Deposits
ATP-17	5	48	45	7	3.8	GP-GM	Vashon Recessional Outwash
ATP-18	4	14	56	30	7.9	SM	Vashon Till
ATP-19	3	NT ¹	NT ¹	89	29.6	ML	Weathered Glaciolacustrine
ATP-21	5	13	28	59	41.1	ML	Vashon Till

Notes:

1. NT – Not tested
2. USCS – Unified Soils Classification System

Landslide Hazards

The results of our review of publicly available resources are as follows:

- The Owl Ridge Parcels is mapped as “Stable,” and described as slopes that generally rise less than 15 percent in grade and are underlain by stable material (Ecology, 1979).
- Analysis using LiDAR maps did not identify this slope as a landslide (McKenna, et al., 2008).
- The geomorphic map indicates a landslide (ls) along the eastern boundary of the Owl Ridge Parcels, meaning there is evidence of a deep-seated landslide as indicated by uphill scarps, bulbous toes, and a position in hillslope hollows (Haugerud, 2009).
- The geologic map is in agreement with the geomorphic map in that a deep-seated rotational landslide is located along the eastern boundary of the Owl Ridge Parcels (Polenz et al, 2013).
- Aspect reviewed the newest publicly available LiDAR data for the Owl Ridge Parcels and surrounding area (DNR, 2019), which shows bowl-shaped topography and hummocky

terrain along the eastern boundary, indicating a possible landslide. None of these features were observed on the Owl Ridge Parcels themselves.

- We reviewed coastal aerial photographs (Ecology, 2025) and aerial photographs (Google, 2025 and NETR, 2025) of the Owl Ridge Parcels area from 1951 through 2024 and did not observe any loss of vegetation that would suggest recent slope movement.

The results of this data review indicate that the Owl Ridge Parcels are not underlain by landslide deposits, but that there may be landslide deposits on the adjoining eastern property. Due to the topography of the area, this landslide is unlikely to put the Project at risk of a landslide.

Conclusions and Recommendations

From our geotechnical investigation, we conclude that the Owl Ridge Parcels is suitable for the proposed residential development, provided the recommendations contained herein are incorporated into the Project design and construction.

Geologically Hazardous Area Considerations

Three geologic hazards are mapped on and within the area of influence of the Owl Ridge Parcels including: high landslide hazard, moderate landslide hazards, and a moderate seismic hazard (Graphic 1). The seismic hazard shape matches the mapped extents of Esperance Sand Member on the geologic map. None of the materials encountered are liquefiable, thus soil liquefaction is not a seismic hazard or design consideration.

The moderate landslide hazard area along the western boundary was fully evaluated during our previous work and we concluded that the area was stable and no setback from the area was needed.

The high landslide hazard along the eastern boundary matches the shape of the deep-seated rotational landslide noted on the geologic and geomorphic maps. Our test pits closest to that boundary did not encounter landslide deposits. It is our opinion that this landslide is currently dormant; therefore, we do NOT recommend a minimum setback from the area; however, this area should be closely monitored during construction by us to confirm no landslide deposits are encountered.

Additional Project Design and Construction Monitoring

All of our previous design and construction recommendations presented in our previous Geotechnical Engineering Report apply to the Owl Ridge Parcels and should be brought to the attention of designers and contractors and incorporated into the Project plans and specifications.

If significant cuts and fills are planned for the Owl Ridge Parcels, we recommend Aspect/Geosyntec be involved during construction, starting with our participation in a pre-construction meeting with you and your contractor. The integrity of the Project and the overall Site and Owl Ridge Parcels stability depends on proper site preparation and construction procedures. In addition, engineering decisions may have to be made in the field in the event that variations in subsurface conditions become apparent.

References

- ASTM International (ASTM), 2022, Annual Book of ASTM Standards, West Conshohocken, Pennsylvania.
- Aspect Consulting, a Geosyntec company (Aspect), 2025, Geotechnical Engineering Report – Johnson Residential Development – Parcel Numbers: 232601-4-001-2009, 242601-3-003-2008, and 252601-2-047-2007 – Poulsbo, Washington, Prepared for: Montebanc Management, LLC, Project No. AS240561-02, February 13, 2025.
- ESM Consulting Engineers LLC (ESM), 2025, Pinnacle at Liberty Bay, Job No. 2090-004-022, PP-06, Sheet 6 of 26, June 13, 2025.
- Google, 2025, Google Earth Pro Program, Years reviewed: 1994, 2004, 2005, 2006, 2007, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2020, 2021, 2022, 2023 and 2024, accessed January 23, 2025.
- Haugerud, R.A. and K.G. Troost (Haugerud and Troost), 2011, Geologic map of the Suquamish 7.5' Quadrangle and part of the Seattle North 7.5' x 15' Quadrangle, Kitsap County, Washington: U.S. Geological Survey Scientific Investigations Map 3181, scale 1:24,000.
- Haugerud, R.A., 2009, Preliminary geomorphic map of the Kitsap Peninsula, Washington, USGS, Open-File Report 2009-1033, Version 1.0, Scale 1:36,000.
- Kitsap County (County), 2025, Kitsap County Parcel Details and Parcel Map Application, <https://psearch.kitsapgov.com/pdetails/default.aspx>, accessed on April 1, 2025.
- McKenna, J.P., D.J. Lidke, and J.A. Coe (McKenna et al.), 2008, Landslides Mapped from LiDAR Imagery, Kitsap County, Washington: U.S. Department of the Interior, U.S. Geological Survey, Open File Report 2008-1292, Version 1.0.
- Nationwide Environmental Title Research, LLC (NETR), 2025, Historical Aerials, Years reviewed: 1951, 1969, 1981, 1994, 2006, 2009, 2011, 2013, 2015, 2017, 2019 and 2021, <https://www.historicaerials.com/>, accessed January 23, 2025.
- Polenz, Michael, Petro, G.T., Contreras, T.A., Stone, K.A., Paulin, G.I., and Cokiar, Recep (Polenz et al.), 2013, Geologic map of the Seabeck and Poulsbo 7.5-minute quadrangles, Kitsap and Jefferson Counties, Washington: Washington Division of Geology and Earth Resources, Map Series 2013-02, scale 1:24,000.
- Washington State Department of Ecology (Ecology), 1979, Coastal Zone Atlas of Washington, Shoreline and Coastal Zone Management Program, Volume 10, <https://fortress.wa.gov/ecy/coastalatlus/tools/Map.aspx>, accessed January 23, 2025.
- Washington State Department of Ecology (Ecology), 2025, Coastal Zone Atlas of Washington, Shoreline Photos from June 10, 1977, May 19, 1992, and July 24, 2016, available at: <https://fortress.wa.gov/ecy/coastalatlus/>, accessed January 23, 2025.

Montebanc Management, LLC
June 16, 2025

Project No. AS240561-03

Washington State Department of Natural Resources (DNR), 2018, Washington Lidar Portal, Olympics South Opsw 2019 DTM hillshade, Kitsap County Opsw 2018 DTM hillshade, and Puget Lowlands 2005 DTM hillshade, lidarportal.dnr.wa.gov, accessed January 23, 2025.

Limitations

Work for this project was performed for Montebanc Management, LLC (Client), and this report was prepared consistent with recognized standards of professionals in the same locality and involving similar conditions, at the time the work was performed. No other warranty, expressed or implied, is made by Aspect Consulting (Aspect).

Recommendations presented herein are based on our interpretation of site conditions, geotechnical engineering calculations, and judgment in accordance with our mutually agreed-upon scope of work. Our recommendations are unique and specific to the project, site, and Client. Application of this report for any purpose other than the project should be done only after consultation with Aspect.

Variations may exist between the soil and groundwater conditions reported and those actually underlying the site. The nature and extent of such soil variations may change over time and may not be evident before construction begins. If any soil conditions are encountered at the site that are different from those described in this report, Aspect should be notified immediately to review the applicability of our recommendations.

Risks are inherent with any site involving slopes and no recommendations, geologic analysis, or engineering design can assure slope stability. Our observations, findings, and opinions are a means to identify and reduce the inherent risks to the Client.

It is the Client's responsibility to see that all parties to this project, including the designer, contractor, subcontractors, and agents, are made aware of this report in its entirety. At the time of this report, design plans and construction methods have not been finalized, and the recommendations presented herein are based on preliminary project information. If project developments result in changes from the preliminary project information, Aspect should be contacted to determine if our recommendations contained in this report should be revised and/or expanded upon.

The scope of work does not include services related to construction safety precautions. Site safety is typically the responsibility of the contractor, and our recommendations are not intended to direct the contractor's site safety methods, techniques, sequences, or procedures. The scope of our work also does not include the assessment of environmental characteristics, particularly those involving potentially hazardous substances in soil or groundwater.

All reports prepared by Aspect for the Client apply only to the services described in the Agreement(s) with the Client. Any use or reuse by any party other than the Client is at the sole risk of that party, and without liability to Aspect. Aspect's original files/reports shall govern in the event of any dispute regarding the content of electronic documents furnished to others.

Please refer to Appendix C titled "Report Limitations and Guidelines for Use" for additional information governing the use of this report.

We appreciate the opportunity to perform these services. If you have any questions please call Alison J. Dennison, LEG, Senior Engineering Geologist at 206-780-7717.

We appreciate the opportunity to perform these services.

Sincerely,

Aspect consulting



6/16/2025

Alison J. Dennison

Alison J. Dennison, LEG
Senior Engineering Geologist
Alison.Dennison@aspectconsulting.com



6/16/2025


Erik O. Andersen, PE
Senior Principal Geotechnical Engineer
Erik.Andersen@aspectconsulting.com

Attachments:

- Figure 1 – Vicinity Map
- Figure 2 – Site Exploration Plan
- Figure 3 – Inferred Geologic Map
- Appendix A – Exploration Logs
- Appendix B – Geotechnical Laboratory Test Results
- Appendix C – Report Limitations and Guidelines for Use

V:\240561 Johnson Residential Development\Deliverables\Johnson Property Geotechnical Report Addendum_2025.06.16 revised.docx

FIGURES




GIS Path: C:\projects\Johnson\Property_240561\Johnson\Property_240561.mxd Site Location Map1 User: haley.dunham 11 April Date: 8/8/2025




<h2 style="margin: 0;">Vicinity Map</h2> <p style="margin: 0;">Geotechnical Engineering Report Addendum Johnson Residential Development Kitsap County Parcel Numbers: 242601-3-018-2001, 242601-3-005-2006, and 242601-3-019-2000 Poulsbo, Washington</p>			FIGURE NO. 1
	MAY-2025 <small>PROJECT NO.</small> AS240561	<small>BY:</small> AJD / HMD <small>REVISED BY:</small> --- / ---	

Data source credits: None | Basemap Service Layer Credits: County of Kitsap, King County, WA State Parks GIS, Esri, TomTom, Garmin, SafeGraph, FAO, METI/NASA, USGS, Bureau of Land Management, EPA, NPS, USFWS, County of Kitsap, Bureau of Land Management, Esri Canada, Esri, HERE, Garmin, INCREMENT P, USGS, METI/NASA, EPA, USDA, Airbus, USGS, NASA, CGIAR, NCEAS, NLS, OS, NMA, Geodatasystems, GSA, GSI and the GIS User Community, Esri, HERE, Garmin, USGS, EPA, NPS



- Aspect Test Pit
- Site Boundary
- Kitsap County Parcels
- Topo Contours 5ft
- Topo Contours 10ft
- Inferred Geologic Contact
- Vashon Recessional Outwash (Qgo)
- Glaciolacustrine Deposits, part of the Pre-Vashon Fines Unit (Qpf)
- Vashon Till (Qvt)



Inferred Geologic Map

Geotechnical Engineering Report
 Johnson Residential Development
 State Route 305
 Poulsbo, Washington



MAY-2025
 PROJECT NO.
 AS240561-02

BY:
 AJD / HMD
 REVISED BY:
 AJD / RAP

FIGURE NO.
3

Data source credits: None || Basemap Service Layer Credits: NA

05 10/25/2024 10:00 AM C:\Users\jason\OneDrive\Documents\Projects\AS240561-02\AS240561-02-10-25-2024\Geologic\Map\1_Sheet_Figure3.aprx | User: Jason | Paper | Plot Date: 5/19/2025

APPENDIX A

Subsurface Exploration Logs

A. Subsurface Explorations

On April 17, 2025, Aspect observed the excavation of eight test pits, ATP-15 through ATP-22. The test pits were excavated by an excavation company provided by you. Test pits were excavated using a Kubota KX040-U tracked excavator. An Aspect representative, Chelsea Bush, LG, was present throughout the field exploration program to determine the locations of the explorations, observe the explorations, assist in sampling, and to prepare descriptive logs of each exploration. Samples were obtained from select soil units to aid in the determination of engineering properties of the subsurface materials and laboratory testing. The locations of explorations are shown on Figure 2 and were collected with a Global Positioning System (GPS).

Detailed descriptions of the subsurface conditions encountered in our explorations, as well as the depths where characteristics of the soils changed, are indicated on the logs presented herein. The depths indicated on the log where conditions changed may represent gradational variations between soil types. Soils were described per the Unified Soils Classification System (USCS) in general accordance with the ASTM International Standard Practice for Description and Identification of Soils (ASTM D2488; ASTM, 2022). The depths on the logs where conditions changed may represent gradational variations between soil types and actual transitions may be more gradual. The subsurface conditions depicted are only for the specific date and locations reported, and therefore, are not necessarily representative of other locations and times. A key to the symbols and terms used on the logs is provided in the Exploration Log Key.

The relative density/consistency of the soils was evaluated qualitatively with a 0.5-inch-diameter steel T-probe and observation of digging difficulty. Relative density was quantitatively assessed with Dynamic Cone Penetrometer Testing (DCPT) at various depth intervals within the test pits. The test pits were backfilled with the excavated soils.

The DCPT method involves a 15-pound steel mass falling 20 inches to strike an anvil, which drives a 1.5-inch-diameter, 45-degree cone into the soil. The number of blows required to drive the cone 1.75 inches is considered one data point. The DCPT data has been calibrated with Standard Penetration Test (SPT, ASTM Method D1586) results to provide a more refined estimate of soil relative density and consistency.

The test pits were backfilled with the excavated soils and tamped into place to reduce the amount of settlement.

Coarse-Grained Soils - More than 50% ¹ Retained on No. 200 Sieve	Gravels - More than 50% ¹ of Coarse Fraction Retained on No. 4 Sieve	≤5% Fines	GW	Well-graded GRAVEL Well-graded GRAVEL WITH SAND	
		≥15% Fines	GP	Poorly-graded GRAVEL Poorly-graded GRAVEL WITH SAND	
	Sands - 50% ¹ or More of Coarse Fraction Passes No. 4 Sieve	≤5% Fines	GM	SILTY GRAVEL SILTY GRAVEL WITH SAND	
		≥15% Fines	GC	CLAYEY GRAVEL CLAYEY GRAVEL WITH SAND	
	Sands - 50% ¹ or More Passes No. 200 Sieve	Sils and Clays Liquid Limit Less than 50%	≤5% Fines	SW	Well-graded SAND Well-graded SAND WITH GRAVEL
			≥15% Fines	SP	Poorly-graded SAND Poorly-graded SAND WITH GRAVEL
≥15% Fines			SM	SILTY SAND SILTY SAND WITH GRAVEL	
Fine-Grained Soils - 50% ¹ or More Passes No. 200 Sieve	Sils and Clays Liquid Limit 50% or More	≥15% Fines	SC	CLAYEY SAND CLAYEY SAND WITH GRAVEL	
		≤5% Fines	ML	SILT SANDY or GRAVELLY SILT SILT WITH SAND SILT WITH GRAVEL	
		≤5% Fines	CL	LEAN CLAY SANDY or GRAVELLY LEAN CLAY LEAN CLAY WITH SAND LEAN CLAY WITH GRAVEL	
	Sils and Clays Liquid Limit 50% or More	≤5% Fines	OL	ORGANIC SILT SANDY or GRAVELLY ORGANIC SILT ORGANIC SILT WITH SAND ORGANIC SILT WITH GRAVEL	
		≤5% Fines	MH	ELASTIC SILT SANDY or GRAVELLY ELASTIC SILT ELASTIC SILT WITH SAND ELASTIC SILT WITH GRAVEL	
		≤5% Fines	CH	FAT CLAY SANDY or GRAVELLY FAT CLAY FAT CLAY WITH SAND FAT CLAY WITH GRAVEL	
Highly Organic Soils	≤5% Fines	OH	ORGANIC CLAY SANDY or GRAVELLY ORGANIC CLAY ORGANIC CLAY WITH SAND ORGANIC CLAY WITH GRAVEL		
	≤5% Fines	PT	PEAT and other mostly organic soils		

"WITH SILT" or "WITH CLAY" means 5 to 15% silt and clay, denoted by a "-" in the group name; e.g., SP-SM • "SILTY" or "CLAYEY" means >15% silt and clay • "WITH SAND" or "WITH GRAVEL" means 15 to 30% sand and gravel. • "SANDY" or "GRAVELLY" means >30% sand and gravel. • "Well-graded" means approximately equal amounts of fine to coarse grain sizes • "Poorly graded" means unequal amounts of grain sizes • Group names separated by "/" means soil contains layers of the two soil types; e.g., SM/ML.

Soils were described and identified in the field in general accordance with the methods described in ASTM D2488. Where indicated in the log, soils were classified using ASTM D2487 or other laboratory tests as appropriate. Refer to the report accompanying these exploration logs for details.

1. Estimated or measured percentage by dry weight
2. (SPT) Standard Penetration Test (ASTM D1586)
3. Determined by SPT, DCPT (ASTM STP399) or other field methods. See report text for details.

MC	=	Natural Moisture Content	GEOTECHNICAL LAB TESTS
PS	=	Particle Size Distribution	
FC	=	Fines Content (% < 0.075 mm)	
GH	=	Hydrometer Test	
AL	=	Atterberg Limits	
C	=	Consolidation Test	
Str	=	Strength Test	
OC	=	Organic Content (% Loss by Ignition)	
Comp	=	Proctor Test	
K	=	Hydraulic Conductivity Test	
SG	=	Specific Gravity Test	

Organic Chemicals			CHEMICAL LAB TESTS
BTEX	=	Benzene, Toluene, Ethylbenzene, Xylenes	
TPH-Dx	=	Diesel and Oil-Range Petroleum Hydrocarbons	
TPH-G	=	Gasoline-Range Petroleum Hydrocarbons	
VOCs	=	Volatile Organic Compounds	
SVOCs	=	Semi-Volatile Organic Compounds	
PAHs	=	Polycyclic Aromatic Hydrocarbon Compounds	
PCBs	=	Polychlorinated Biphenyls	
Metals			
RCRA8	=	As, Ba, Cd, Cr, Pb, Hg, Se, Ag, (d = dissolved, t = total)	
MTCA5	=	As, Cd, Cr, Hg, Pb (d = dissolved, t = total)	
PP-13	=	Ag, As, Be, Cd, Cr, Cu, Hg, Ni, Pb, Sb, Se, Tl, Zn (d=dissolved, t=total)	

PID	=	Photoionization Detector	FIELD TESTS
Sheen	=	Oil Sheen Test	
SPT ²	=	Standard Penetration Test	
NSPT	=	Non-Standard Penetration Test	
DCPT	=	Dynamic Cone Penetration Test	

Descriptive Term	Size Range and Sieve Number	COMPONENT DEFINITIONS
Boulders	= Larger than 12 inches	
Cobbles	= 3 inches to 12 inches	
Coarse Gravel	= 3 inches to 3/4 inches	
Fine Gravel	= 3/4 inches to No. 4 (4.75 mm)	
Coarse Sand	= No. 4 (4.75 mm) to No. 10 (2.00 mm)	
Medium Sand	= No. 10 (2.00 mm) to No. 40 (0.425 mm)	
Fine Sand	= No. 40 (0.425 mm) to No. 200 (0.075 mm)	
Silt and Clay	= Smaller than No. 200 (0.075 mm)	

% by Weight	Modifier	% by Weight	Modifier	ESTIMATED¹ PERCENTAGE
<1	=	Subtrace	15 to 25 = Little	
1 to <5	=	Trace	30 to 45 = Some	
5 to 10	=	Few	>50 = Mostly	

Dry	=	Absence of moisture, dusty, dry to the touch	MOISTURE CONTENT
Slightly Moist	=	Perceptible moisture	
Moist	=	Damp but no visible water	
Very Moist	=	Water visible but not free draining	
Wet	=	Visible free water, usually from below water table	

Non-Cohesive or Coarse-Grained Soils			RELATIVE DENSITY
Density³	SPT² Blows/Foot	Penetration with 1/2" Diameter Rod	
Very Loose	= 0 to 4	≥ 2'	
Loose	= 5 to 10	1' to 2'	
Medium Dense	= 11 to 30	3" to 1'	
Dense	= 31 to 50	1" to 3"	
Very Dense	= > 50	< 1"	

Cohesive or Fine-Grained Soils			CONSISTENCY
Consistency³	SPT² Blows/Foot	Manual Test	
Very Soft	= 0 to 1	Penetrated >1" easily by thumb. Extrudes between thumb & fingers.	
Soft	= 2 to 4	Penetrated 1/4" to 1" easily by thumb. Easily molded.	
Medium Stiff	= 5 to 8	Penetrated >1/4" with effort by thumb. Molded with strong pressure.	
Stiff	= 9 to 15	Indented ~1/4" with effort by thumb.	
Very Stiff	= 16 to 30	Indented easily by thumbnail.	
Hard	= > 30	Indented with difficulty by thumbnail.	

GEOLOGIC CONTACTS		
Observed and Distinct	Observed and Gradual	Inferred

	Exploration Log Key
---	---------------------



Johnson Property - AS240561

Project Address & Site Specific Location
Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
47.7230, -122.6255 (est)
Ground Surface Elev. (NAVD88)
195' (est)

Exploration Number

ATP-15

Contractor
Freedom Boring &
Excavating

Equipment
Kubota KX040-4

Sampling Method
Grab

Operator

Exploration Method(s)

Work Start/Completion Dates

Top of Casing Elev. (NAVD88)

Depth to Water (Below GS)

Neil

Trackhoe

4/17/2025

NA

2.5' (Seep)

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot					Blows/6'	Tests	Material Type	Description	Depth (ft)		
				0	10	20	30	40						50	
1	194	Exploration backfilled with excavated materials, tamped in place. 4/17/2025										TOPSOIL SILT WITH SAND (ML); loose, moist, brown; small roots, some organics.	1		
2	193												HIGHLY WEATHERED GLACIOLACUSTRINE DEPOSITS SILT WITH SAND (ML); medium dense, moist, light brown; fine to coarse sand; iron-oxide staining.	2	
3	192													3	
4	191												WEATHERED GLACIOLACUSTRINE DEPOSITS SILT WITH SAND (ML); dense, moist, gray.	4	
5	190													5	
6	189													6	
7	188													7	
8	187												UNWEATHERED GLACIOLACUSTRINE DEPOSITS SILT WITH SAND (ML); very dense, moist, blue gray.	8	
9	186													9	
10	185				S1										10
11	184												Bottom of exploration at 11 ft. bgs. Note: Test pit excavated prior to arrival. No test pit caving observed.	11	
12	183											12			
13	182											13			
14	181											14			

Legend

Grab sample

Plastic Limit ——— Liquid Limit

Water Level (Seepage)

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
Approved by: AJD 5/14/2025

Exploration Log ATP-15

Sheet 1 of 1

NEW STANDARD EXPLORATION LOG TEMPLATE P:\GINT\PROJECTS\AS240561 JOHNSON PROPERTY POULSBO.GPJ May 15, 2025



Johnson Property - AS240561

Project Address & Site Specific Location
 Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
 47.7233, -122.6255 (est)
 Ground Surface Elev. (NAVD88)
 238' (est)

Exploration Number

ATP-16

Contractor
 Freedom Boring &
 Excavating

Equipment
 Kubota KX040-4

Sampling Method
 Grab

Operator

Exploration Method(s)

Work Start/Completion Dates

Top of Casing Elev. (NAVD88)

Depth to Water (Below GS)

Neil

Trackhoe

4/17/2025

NA

No Water Encountered

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot Water Content (%)					Blows/6'	Tests	Material Type	Description	Depth (ft)	
				0	10	20	30	40						50
1	237	Exploration backfilled with excavated materials, tamped in place.	S1							DCPT =8,10,12 PS,MC FC=8%	TOPSOIL SILT (ML); loose, moist, dark brown; abundant organics.	1		
2	236			12.6								VASHON RECESSONAL OUTWASH SAND WITH SILT (SP-SM); medium dense, moist, light brown; iron-oxide staining; few small roots.	2	
3	235											Becomes without roots.	3	
4	234											DCPT =10,8,14		4
5	233				S2							FC, MC FC=66%	WEATHERED GLACIOLACUSTRINE DEPOSITS SANDY SILT (ML); dense, moist, gray brown.	5
6	232													6
7	231													7
8	230												UNWEATHERED GLACIOLACUSTRINE DEPOSITS SANDY SILT (ML); very dense, moist, blue gray.	8
9	229													9
10	228												Bottom of exploration at 9.5 ft. bgs. Note: No test pit caving observed.	10
11	227													11
12	226													12
13	225													13
14	224													14

Legend

Grab sample

Plastic Limit — Liquid Limit

No Water Encountered

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
 Approved by: AJD 5/14/2025

Exploration Log ATP-16

Sheet 1 of 1



Johnson Property - AS240561

Project Address & Site Specific Location
Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
47.7238, -122.6258 (est)
Ground Surface Elev. (NAVD88)
275' (est)

Exploration Number

ATP-17

Contractor
Freedom Boring & Excavating

Equipment
Kubota KX040-4

Sampling Method
Grab

Operator

Exploration Method(s)

Work Start/Completion Dates

Top of Casing Elev. (NAVD88)

Depth to Water (Below GS)

Neil

Trackhoe

4/17/2025

NA

No Water Encountered

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot					Blows/6'	Tests	Material Type	Description	Depth (ft)
				0	10	20	30	40					
1	274	Exploration backfilled with excavated materials, tamped in place.									TOPSOIL SILT (ML); loose, moist, dark brown; abundant organics.	1	
2	273									T-probe = 4 inches	VASHON RECESSONAL OUTWASH SAND WITH SILT, GRAVEL, AND COBBLES (SP-SM); medium dense, moist, brown; fine to coarse sand; fine to coarse, subrounded gravel; up to 5-inch-diameter subrounded cobbles; iron-oxide staining; roots up to 2-inch-diameter.	2	
3	272									DCPT =9,12,17	GRAVEL WITH SILT, SAND, COBBLES, AND BOULDERS (GP-GM); medium dense, moist, brown; fine to coarse sand; fine to coarse, subangular to subrounded gravel; up to 5-inch-diameter subangular cobbles.	3	
4	271												4
5	270										PS, MC FC=7%	Becomes very moist, gray.	5
6	269												6
7	268											Becomes dense, moist; fine to coarse sand; fine to coarse, subangular to subrounded gravel; up to 8-inch-diameter subangular to subrounded cobbles. Boulder observed at 7 feet bgs.	7
8	267												8
9	266												9
10	265											Bottom of exploration at 9.5 ft. bgs. Note: No test pit caving observed.	10
11	264												11
12	263												12
13	262												13
14	261												14

Legend

Grab sample

Plastic Limit | Liquid Limit

No Water Encountered

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
Approved by: AJD 5/14/2025

Exploration Log ATP-17

Sheet 1 of 1



Johnson Property - AS240561

Project Address & Site Specific Location
Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
47.7238, -122.6247 (est)
Ground Surface Elev. (NAVD88)
267' (est)

Exploration Number

ATP-18

Contractor
Freedom Boring & Excavating

Equipment
Kubota KX040-4

Sampling Method
Grab

Operator

Exploration Method(s)

Work Start/Completion Dates

Top of Casing Elev. (NAVD88)

Depth to Water (Below GS)

Neil

Trackhoe

4/17/2025

NA

No Water Encountered

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot					Blows/6'	Tests	Material Type	Description	Depth (ft)	
				0	10	20	30	40						50
1	266	Exploration backfilled with excavated materials, tamped in place.	S1							DCPT =4,21,30 PS, MC FC=30%		TOPSOIL SILT WITH SAND (ML); loose, moist, dark brown; abundant organics; small roots.	1	
2	265											VASHON TILL SAND WITH SILT, GRAVEL, AND COBBLES (SP-SM); medium dense, moist, brown; fine to coarse sand; fine to coarse, subrounded gravel; up to 5-inch-diameter subrounded cobbles; iron-oxide staining; roots up to 2-inch-diameter.	2	
3	264											SILTY SAND (SM); very dense, moist, gray; fine to coarse sand; fine to coarse, subangular to subrounded gravel; gravel socketed in matrix.	3	
4	263													4
5	262													5
6	261										Bottom of exploration at 5 ft. bgs. Note: No test pit caving observed.	6		
7	260											7		
8	259											8		
9	258											9		
10	257											10		
11	256											11		
12	255											12		
13	254											13		
14	253											14		

Legend

Grab sample

Plastic Limit | Liquid Limit

No Water Encountered

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
Approved by: AJD 5/14/2025

Exploration Log ATP-18

Sheet 1 of 1



Johnson Property - AS240561

Project Address & Site Specific Location
Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
47.7235, -122.6233 (est)
Ground Surface Elev. (NAVD88)
234' (est)

Exploration Number

ATP-19

Contractor
Freedom Boring & Excavating

Equipment
Kubota KX040-4

Sampling Method
Grab

Operator

Exploration Method(s)

Work Start/Completion Dates

Top of Casing Elev. (NAVD88)

Depth to Water (Below GS)

Neil

Trackhoe

4/17/2025

NA

No Water Encountered

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot					Blows/6'	Tests	Material Type	Description	Depth (ft)		
				0	10	20	30	40						50	
1	233	Exploration backfilled with excavated materials, tamped in place.	S1							DCPT =8,17,20 FC,MC FC=89%	TOPSOIL SILT (ML); loose, moist, dark brown; abundant organics.	1			
2	232											HIGHLY WEATHERED GLACIOLACUSTRINE DEPOSITS SANDY SILT WITH GRAVEL (ML); medium dense, very moist, gray brown; fine to coarse sand; fine to coarse, subangular to subrounded gravel; iron-oxide staining along fractures. Becomes very moist.	2		
3	231													3	
4	230													UNWEATHERED GLACIOLACUSTRINE DEPOSITS SILT WITH SAND (ML); dense, moist, gray brown; fine to medium sand.	4
5	229														5
6	228														6
7	227														7
8	226														8
9	225														9
10	224										Bottom of exploration at 9 ft. bgs. Note: No test pit caving observed.	10			
11	223											11			
12	222											12			
13	221											13			
14	220											14			

Legend

Grab sample

Plastic Limit | Liquid Limit

No Water Encountered

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
Approved by: AJD 5/14/2025

Exploration Log ATP-19

Sheet 1 of 1



Johnson Property - AS240561

Project Address & Site Specific Location
Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
47.7237, -122.6227 (est)
Ground Surface Elev. (NAVD88)
267' (est)

Exploration Number

ATP-20

Contractor
Freedom Boring &
Excavating

Equipment
Kubota KX040-4

Sampling Method
Grab

Operator

Exploration Method(s)
Trackhoe

Work Start/Completion Dates
4/17/2025

Top of Casing Elev. (NAVD88)
NA

Depth to Water (Below GS)
No Water Encountered

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot					Blows/6'	Tests	Material Type	Description	Depth (ft)
				0	10	20	30	40					
1	266	Exploration backfilled with excavated materials, tamped in place.									TOPSOIL SILT WITH SAND (ML); loose, moist, dark brown; abundant organics.	1	
2	265											HIGHLY WEATHERED GLACIOLACUSTRINE DEPOSITS SILT WITH SAND (ML); medium dense, very moist, brown; fine to medium sand; iron-oxide staining along fractures.	2
3	264									DCPT =4,11,13		3	
4	263											WEATHERED GLACIOLACUSTRINE DEPOSITS SILT WITH SAND (ML); dense, very moist, gray; fine to medium sand; iron-oxide staining along fractures.	4
5	262												5
6	261												6
7	260												7
8	259										Bottom of exploration at 7.5 ft. bgs. Note: No test pit caving observed.	8	
9	258											9	
10	257											10	
11	256											11	
12	255											12	
13	254											13	
14	253											14	

Legend

Plastic Limit | Liquid Limit

No Water Encountered

Sample Type

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
Approved by: AJD 5/14/2025

Exploration Log ATP-20

Sheet 1 of 1



Johnson Property - AS240561

Project Address & Site Specific Location
 Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
 47.7232, -122.6232 (est)
 Ground Surface Elev. (NAVD88)
 222' (est)

Exploration Number

ATP-21

Contractor
 Freedom Boring &
 Excavating

Equipment
 Kubota KX040-4

Sampling Method
 Grab

Operator

Exploration Method(s)

Work Start/Completion Dates

Top of Casing Elev. (NAVD88)

Depth to Water (Below GS)

Neil

Trackhoe

4/17/2025

NA

No Water Encountered

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot					Blows/6'	Tests	Material Type	Description	Depth (ft)	
				0	10	20	30	40						50
1	221	Exploration backfilled with excavated materials, tamped in place.	S1							DCPT =7,13,9	TOPSOIL SILT WITH SAND (ML); loose, moist, dark brown; fine to medium sand; up to 2 inch diameter roots.	1		
2	220											VASHON TILL SILT WITH SAND (ML); medium dense, moist, brown; fine to coarse sand; trace fine to coarse, subrounded gravel; iron-oxide staining.	2	
3	219												Becomes without roots.	3
4	218												SILT WITH SAND (ML); dense, moist, gray; fine to coarse sand; trace fine to coarse, subrounded gravel; iron-oxide staining.	4
5	217											PS, MC FC=59%		SILTY SAND WITH GRAVEL AND COBBLES (SM); dense, moist, gray brown; fine to coarse sand; fine to coarse, subangular to rounded gravel; up to 6-inch-diameter, subangular to subrounded cobbles; gravel and cobbles socketed in matrix.
6	216												Bottom of exploration at 6 ft. bgs.	
7	215									Note: No test pit caving observed.	7			
8	214										8			
9	213										9			
10	212										10			
11	211										11			
12	210										12			
13	209										13			
14	208										14			

Legend

Grab sample

Plastic Limit | Liquid Limit

No Water Encountered

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
 Approved by: AJD 5/14/2025

Exploration Log
ATP-21

Sheet 1 of 1

NEW STANDARD EXPLORATION LOG TEMPLATE P:\GINT\PROJECTS\AS240561 JOHNSON PROPERTY POULSBO.GPJ May 15, 2025



Johnson Property - AS240561

Project Address & Site Specific Location
 Poulsbo, WA, See Figure 2.

Geotechnical Exploration Log

Coordinates (Lat, Lon WGS84)
 47.7228, -122.6242 (est)
 Ground Surface Elev. (NAVD88)
 190' (est)

Exploration Number

ATP-22

Contractor
 Freedom Boring &
 Excavating

Equipment
 Kubota KX040-4

Sampling Method
 Grab

Operator

Exploration Method(s)

Work Start/Completion Dates

Top of Casing Elev. (NAVD88)

Depth to Water (Below GS)

Neil

Trackhoe

4/17/2025

NA

No Water Encountered

Depth (feet)	Elev. (feet)	Exploration Notes and Completion Details	Sample Type/ID	Blows/foot					Blows/6'	Tests	Material Type	Description	Depth (ft)		
				0	10	20	30	40						50	
1	189	Exploration backfilled with excavated materials, tamped in place.	S1							DCPT =8, 15, 9	[Material Type Icon]	TOPSOIL SILTY SAND WITH GRAVEL (SM); loose, moist, dark brown; fine to coarse sand; fine to coarse, subangular to subrounded gravel; organics; up to 1-inch-diameter roots.	1		
2	188											VASHON TILL SANDY SILT WITH GRAVEL (ML); loose, wet, gray brown; fine to coarse sand; trace fine to coarse, subrounded gravel; up to 5-inch-diameter cobbles; iron-oxide staining.	2		
3	187												3		
4	186											Becomes dense, moist, gray brown.	4		
5	185												5		
6	184												6		
7	183				S2									Becomes with 0.1- to 0.2-inch-thick SAND partings.	7
8	182				S3									Becomes very moist.	8
9	181									Bottom of exploration at 8.5 ft. bgs. Note: No test pit caving observed.	9				
10	180										10				
11	179										11				
12	178										12				
13	177										13				
14	176										14				

Legend

[Hand icon] Grab sample

Plastic Limit | Liquid Limit

No Water Encountered

Water Level

See Exploration Log Key for explanation of symbols

Logged by: CB
 Approved by: AJD 5/14/2025

Exploration Log
ATP-22

Sheet 1 of 1

NEW STANDARD EXPLORATION LOG TEMPLATE P:\GINT\PROJECTS\AS240561 JOHNSON PROPERTY POULSBO.GPJ May 15, 2025

APPENDIX B

Geotechnical Laboratory Testing Results

B. Geotechnical Laboratory Testing Results

Geotechnical laboratory tests were conducted on selected soil samples collected during the field exploration program. The tests performed, and the procedures followed, are outlined below. The laboratory tests were conducted in general accordance with appropriate ASTM International (ASTM) test methods and were conducted by AAR Testing and Inspection, Inc., an accredited laboratory in Redmond, Washington.

B.1. Moisture Content Determination, MC

All four samples submitted for particle-size analyses and the two samples submitted for fines content determination were analyzed for water content by the ASTM D 2216 test method. This test method allows for the laboratory determination of the moisture (water) content of a soil sample by measuring and recording the mass of a sample before and then after drying. Test results are illustrated graphically on the logs in Appendix A.

B.2. Particle-Size Analyses, PF

Two select soil samples were submitted for particle-size with #200 sieve analysis in general accordance with ASTM D-2216, D-2419, D-4318, and D-5821 methods. This test method allows for the laboratory determination of the percent of the size fractions (by weight) of coarse-grained soil and the percent of fines in a soil sample, as well as the grain size diameter percentages of the material. The result of the test is presented in this appendix as curves depicting the percent finer by weight versus particle size.


B.3. Fines Content Determination, FC

The fines content was determined on four selected soil samples in general accordance with ASTM D1140. The results of the tests are shown in the table below, on the exploration logs, and tabulated in this appendix.

These results are for the exclusive use of the client for whom they were obtained. They apply only to the samples tested and are not indicative of apparently identical samples.

Particle Size Distribution Report

ASTM C117 & C136



% +3"	% Gravel		% Sand			% Fines	
	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
0	0	1	1	29	61	8	

Test Results (ASTM C117 & C136)				
Sieve Size or Diam. (mm.)	Finer (%)	Spec. * (%)	Out of Spec. (%)	Pct. of Fines
1 1/2	100			
1	100			
3/4	100			
1/2	100			
3/8	100			
#4	99			
#10	98			
#20	93			
#40	69			
#60	30			
#80	17			
#100	13			
#200	7.8			

* (no specification provided)

Material Description

Poorly graded sand with silt

Atterberg Limits
 PL= LL= PI=

Coefficients
 D₉₀= 0.7473 D₈₅= 0.6181 D₆₀= 0.3696
 D₅₀= 0.3271 D₃₀= 0.2517 D₁₅= 0.1695
 D₁₀= 0.1132 C_u= 3.26 C_c= 1.51

Classification
 USCS= SP-SM AASHTO=

Test Remarks
 As Received Moisture: 12.6%
 F.M.=1.67

Source of Sample: ATP-16; S1
Sample Number: 27917

Depth: 2

Sample Date: 04/17/2025

AAR Testing and Inspection, Inc.	Client: Geosyntec Consultants, Inc. Project: Johnson Owl Ridge, AS240561 Project No: 25-287
---	---


Tested By: Tama Lewis #60698

Checked By: Stu Swenson, CET

These results are for the exclusive use of the client for whom they were obtained. They apply only to the samples tested and are not indicative of apparently identical samples.

Particle Size Distribution Report

ASTM C117 & C136



% +3"	% Gravel		% Sand			% Fines	
	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
0	11	37	12	13	20	7	

Test Results (ASTM C117 & C136)				
Sieve Size or Diam. (mm.)	Finer (%)	Spec. * (%)	Out of Spec. (%)	Pct. of Fines
1 1/2	100			
1	97			
3/4	89			
1/2	74			
3/8	68			
#4	52			
#10	40			
#20	33			
#40	27			
#60	18			
#80	14			
#100	12			
#200	6.9			

* (no specification provided)

Material Description

Poorly graded gravel with silt and sand

Atterberg Limits
 PL= LL= PI=

Coefficients
 D₉₀= 19.7381 D₈₅= 17.1663 D₆₀= 6.7325
 D₅₀= 4.1282 D₃₀= 0.5806 D₁₅= 0.1968
 D₁₀= 0.1217 C_u= 55.34 C_c= 0.41

Classification
 USCS= GP-GM AASHTO=

Test Remarks

As Received Moisture: 3.8%
F.M.=4.50

Source of Sample: ATP-17; S1
Sample Number: 27919

Depth: 5

Sample Date: 04/17/2025

AAR Testing and Inspection, Inc.	Client: Geosyntec Consultants, Inc. Project: Johnson Owl Ridge, AS240561 Project No: 25-287
---	---


Tested By: Tama Lewis #60698

Checked By: Stu Swenson, CET

These results are for the exclusive use of the client for whom they were obtained. They apply only to the samples tested and are not indicative of apparently identical samples.

Particle Size Distribution Report

ASTM C117 & C136



% +3"	% Gravel		% Sand			% Fines	
	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
0	4	10	6	15	35	30	

Test Results (ASTM C117 & C136)				
Sieve Size or Diam. (mm.)	Finer (%)	Spec. * (%)	Out of Spec. (%)	Pct. of Fines
1 1/2	100			
1	100			
3/4	96			
1/2	95			
3/8	92			
#4	86			
#10	80			
#20	74			
#40	65			
#60	51			
#80	44			
#100	40			
#200	30			

Material Description

Silty sand

Atterberg Limits

PL= LL= PI=

Coefficients

D₉₀= 7.6977 D₈₅= 4.3545 D₆₀= 0.3439
D₅₀= 0.2358 D₃₀= 0.0774 D₁₅=
D₁₀= C_u= C_c=

Classification

USCS= SM AASHTO=

Test Remarks

As Received Moisture: 7.9%
F.M.=2.02

* (no specification provided)

Source of Sample: ATP-18; S1
Sample Number: 27920

Depth: 4

Sample Date: 04/17/2025

AAR Testing and Inspection, Inc.	Client: Geosyntec Consultants, Inc. Project: Johnson Owl Ridge, AS240561 Project No: 25-287
---	---


Tested By: Tama Lewis #60698

Checked By: Stu Swenson, CET

These results are for the exclusive use of the client for whom they were obtained. They apply only to the samples tested and are not indicative of apparently identical samples.

Particle Size Distribution Report

ASTM C117 & C136



% +3"	% Gravel		% Sand			% Fines	
	Coarse	Fine	Coarse	Medium	Fine	Silt	Clay
0	3	10	4	7	17	59	

Test Results (ASTM C117 & C136)				
Sieve Size or Diam. (mm.)	Finer (%)	Spec. * (%)	Out of Spec. (%)	Pct. of Fines
1 1/2	100			
1	100			
3/4	97			
1/2	94			
3/8	91			
#4	87			
#10	83			
#20	80			
#40	76			
#60	71			
#80	69			
#100	67			
#200	59			

Material Description

Sandy silt

Atterberg Limits

PL= LL= PI=

Coefficients

D₉₀= 7.8918 D₈₅= 3.4619 D₆₀= 0.0822
D₅₀= D₃₀= D₁₅=
D₁₀= C_u= C_c=

Classification

USCS= ML AASHTO=

Test Remarks

As Received Moisture: 14.1%
F.M.=1.43

* (no specification provided)

Source of Sample: ATP-21; S1
Sample Number: 27922

Depth: 5

Sample Date: 04/17/2025

AAR Testing and Inspection, Inc.	Client: Geosyntec Consultants, Inc. Project: Johnson Owl Ridge, AS240561 Project No: 25-287
---	---

Tested By: Tama Lewis #60698

Checked By: Stu Swenson, CET

APPENDIX C

Report Limitations and Guidelines for Use

REPORT LIMITATIONS AND GUIDELINES FOR USE

Geoscience is Not Exact

The geoscience practices (geotechnical engineering, geology, and environmental science) are far less exact than other engineering and natural science disciplines. It is important to recognize this limitation in evaluating the content of the report. If you are unclear how these "Report Limitations and Guidelines for Use" apply to your project or property, you should contact Aspect Consulting (Aspect).

This Report and Project-Specific Factors

Aspect's services are designed to meet the specific needs of our clients. Aspect has performed the services in general accordance with our agreement (the Agreement) with the Client (defined under the Limitations section of this project's work product). This report has been prepared for the exclusive use of the Client. This report should not be applied for any purpose or project except the purpose described in the Agreement.

Aspect considered many unique, project-specific factors when establishing the Scope of Work for this project and report. You should not rely on this report if it was:

- Not prepared for you;
- Not prepared for the specific purpose identified in the Agreement;
- Not prepared for the specific subject property assessed; or
- Completed before important changes occurred concerning the subject property, project, or governmental regulatory actions.

If changes are made to the project or subject property after the date of this report, Aspect should be retained to assess the impact of the changes with respect to the conclusions contained in the report.

Reliance Conditions for Third Parties

This report was prepared for the exclusive use of the Client. No other party may rely on the product of our services unless we agree in advance to such reliance in writing. This is to provide our firm with reasonable protection against liability claims by third parties with whom there would otherwise be no contractual limitations. Within the limitations of scope, schedule, and budget, our services have been executed in accordance with our Agreement with the Client and recognized geoscience practices in the same locality and involving similar conditions at the time this report was prepared.

Property Conditions Change Over Time

This report is based on conditions that existed at the time the study was performed. The findings and conclusions of this report may be affected by the passage of time, by events such as a change in property use or occupancy, or by natural events, such as floods, earthquakes, slope instability, or groundwater fluctuations. If any of the described events may have occurred following the issuance of the report, you should contact Aspect so that we may evaluate whether changed conditions affect the continued reliability or applicability of our conclusions and recommendations.

Geotechnical, Geologic, and Environmental Reports Are Not Interchangeable

The equipment, techniques, and personnel used to perform a geotechnical or geologic study differ significantly from those used to perform an environmental study and vice versa. For that reason, a geotechnical engineering or geologic report does not usually address any environmental findings, conclusions, or recommendations (e.g., about the likelihood of encountering underground storage tanks or regulated contaminants). Similarly, environmental reports are not used to address geotechnical or geologic concerns regarding the subject property.

We appreciate the opportunity to perform these services. If you have any questions, please contact the Aspect Project Manager for this project.